LIGHTING LED BATTENS & TUBES







UNI SERIESIP65 BATTEN SERIES

The Uni IP65 Batten Series is waterproof, IK10 impact resistant and designed as the ideal upgrade product to replace existing surface mounted or suspended fluorescent battens in outdoor locations.

The IP65 Batten includes switch controlled tri-colour temperature options, an adjustable built-in motion sensor and the option to add an emergency backup battery.

FEATURES

- Ideal for outside locations
- IP65 and IK10 rating
- Optional maintained emergency light
- Sensor with adjustable dim levels and hold times
- Tri-colour

SPECIFICATIONS

POWER FACTOR	>0.9			
CRI	>80			
BEAM ANGLE	120°			
IP RATING	65			
LIFETIME (L ₇₀)	>60,000hrs			
WARRANTY	5 Years			

SENSOR SETTINGS

DETECTION RANGE	5 or 10 metres
HOLD TIME	1m, 5m, 15mins or infinite
DAYLIGHT SENSOR	50Lux or disabled
STANDBY PERIOD	Os, 5m , 30m or infinite
STANDBY LEVEL	10 , 20, 30 or 50%

Highlighted values = sensor default settings

LPM = LCP LOW POWER MODE

MODEL NUMBER	ССТ	DIMENSIONS	WATT	LCP	LPM	LUMENS	EFFICACY		
IP65 TRI-COLOUF	₹								
EP-UNI-T665-18	4/5/6000K	74x116x600mm	18	18.23		2313	127lm/W		
EP-UNI-T1265-25	4/5/6000K	74x116x1200mm	25	23.82		3261	137lm/W		
IP65 TRI-COLOUR WITH SENSOR									
EP-UNI-TS665-18	4/5/6000K	74x115x600mm	18	17.4	2.57	2214	127lm/W		
EP-UNI-TS1265-25	4/5/6000K	74x116x1200mm	25	24.94	2.72	3287	132lm/W		





EEIS Approved ACT REES Approved SA





